



ELECTRICAL SPARE PART | PIEZA ELÉCTRICA

DIODE | DIODO

DIODE GA1008-POS / GA1008-NEG


FEATURES / CARACTERÍSTICAS:
 19V~24V | 70A | Diameter: 12,8 mm
Avalanche Type
 Package: 10 units
APPLICATION / APLICACIÓN:
 ...

DIODE GA1009-POS / GA1009-NEG


FEATURES / CARACTERÍSTICAS:
 32V~40V | 70A | Diameter: 12,8 mm
Avalanche Type
 Package: 10 units
APPLICATION / APLICACIÓN:
 ...

DIODE GA1100-POS / GA1101-NEG


FEATURES / CARACTERÍSTICAS:
 400V | 35A | Diameter: 12,8 mm
Press-fit type Wapsa Heavy Duty
 Package: 10 units
APPLICATION / APLICACIÓN:
 Alternators WAPSA / BOSCH.

DIODE GA1103-POS


FEATURES / CARACTERÍSTICAS:
 400V | 35A | Diameter: 12,8 mm
Press-fit type Wapsa Heavy Duty
 Package: 10 units
APPLICATION / APLICACIÓN:
 Alternators WAPSA / BOSCH.

DIODE GA1104-POS / GA1105-NEG


FEATURES / CARACTERÍSTICAS:
 400V | 35A | Diameter: 12,8 mm
Press-fit type Wapsa Heavy Duty type flag female terminal
 Package: 10 units
APPLICATION / APLICACIÓN:
 Alternators WAPSA / BOSCH.

DIODE GA1106-POS / GA1107-NEG


FEATURES / CARACTERÍSTICAS:
 400V | 35A | Diameter: 12,8 mm
Press-fit type Wapsa Heavy Duty
 Package: 10 units
APPLICATION / APLICACIÓN:
 Alternators BOSCH.

DIODE GA1108-POS


FEATURES / CARACTERÍSTICAS:
 400V | 35A | Diameter: 12,8 mm
Press-fit type Bosch Heavy Duty
 Package: 10 units
APPLICATION / APLICACIÓN:
 Alternators BOSCH.

DIODE GA1109-POS / GA1110-NEG


FEATURES / CARACTERÍSTICAS:
 400V | 35A | Diameter: 8,75mm
Diode type Tin Can
 Package: 10 units
APPLICATION / APLICACIÓN:
 Many imported vehicles.

DIODE GA1112-POS / GA1113-NEG


FEATURES / CARACTERÍSTICAS:
 400V | 50A | Diameter: 12,8 mm
Press-fit type Bosch Extra Heavy Duty
 Package: 10 units
APPLICATION / APLICACIÓN:
 Alternators BOSCH.

DIODE GA1114P-POS / GA1114N-NEG


FEATURES / CARACTERÍSTICAS:
 200V | 35A
Diode type Mitsubishi
 Package: 10 units
APPLICATION / APLICACIÓN:
 Alternators MANDO, MITSUBISHI, MIDO.

DIODE GA1115P-POS / GA1115N-NEG


FEATURES / CARACTERÍSTICAS:
 400V | 50A | Diameter: 11,5mm
Extra Heavy Duty
 Package: 10 units
REPLACES / REEMPLAZA
 Cargo: 136253, 136254
APPLICATION / APLICACIÓN:
 Alternators HITACHI.

DIODE GA1102


FEATURES / CARACTERÍSTICAS:
 800V | 3A
Excitation Diode
 Package: 10 units
APPLICATION / APLICACIÓN:

DIODE GA1121P-POS / GA1121N-NEG


FEATURES / CARACTERÍSTICAS:
 24V~32V | 35A Avalanche (Zener) | Diameter: 12,8 mm
Press-fit Bosch
 Package: 10 units
APPLICATION / APLICACIÓN:

DIODE GA1122P-POS / GA1122N-NEG


FEATURES / CARACTERÍSTICAS:
 38V~42V | 35A Avalanche (Zener) | Diameter: 12,8 mm
Press-fit Bosch
 Package: 10 units
APPLICATION / APLICACIÓN:

DIODE GA1123P-POS / GA1123N-NEG


FEATURES / CARACTERÍSTICAS:
 24V~32V | 50A | Avalanche (Zener) | Diameter: 12,8 mm
 Press-fit Bosch
 Package: 10 units
APPLICATION / APLICACIÓN:

DIODE GA1124P-POS / GA1124N-NEG


FEATURES / CARACTERÍSTICAS:
 38V~42V | 50A | Avalanche (Zener) | Diameter: 12,8 mm
 Pressfit Bosch
 Package: 10 units
APPLICATION / APLICACIÓN:

DIODE GA1125P-POS / GA1125N-NEG


FEATURES / CARACTERÍSTICAS:
 24V~32V | 50A | Avalanche (Zener) | Diameter: 10 mm
 Press-fit Lucas
 Package: 10 units
APPLICATION / APLICACIÓN:

DIODE GA1352-35A / GA1502-50A


FEATURES / CARACTERÍSTICAS:
 400V
 Diodes type Button
 Package: 10 units
APPLICATION / APLICACIÓN:

DIODE TRIO GA1002


FEATURES / CARACTERÍSTICAS:
 800V | 3A
 Diodes excit.
 Package: 1 unit
APPLICATION / APLICACIÓN:
 Replaces: Bosch: 1 121 099 005 Alternators Diversos

DIODE TRIO GA1005


FEATURES / CARACTERÍSTICAS:
 800V | 3A
 Diodes excit. Compatible with GA1006
 Package: 1 unit
APPLICATION / APLICACIÓN:
 Replaces: Bosch: 9 121 450 594, Wapsa: 436-01 Alternators: Wapsa.

DIODE TRIO GA1116


FEATURES / CARACTERÍSTICAS:
 200V | 2.5A
 Package: 10 units
APPLICATION / APLICACIÓN:
 Alternators type Magneti Marelli

DIODE TRIO GA1117


FEATURES / CARACTERÍSTICAS:
 200V | 2.5A
 Package: 10 units
APPLICATION / APLICACIÓN:
 Alternators type Magneti Marelli
 P.S: without connector. GA1116 with connector

DIODE TRIO GA1220


FEATURES / CARACTERÍSTICAS:
 600V | 3A
 Package: 10 units.
APPLICATION / APLICACIÓN:
 Replaces: **Delco**: 1.984.032, 3.472.312, 7.982.635, GM: 52.278.220. Alternators: 11S de 28A à 55A, Chevete, Opala, Utilitários.

DIODE TRIO GA1221


FEATURES / CARACTERÍSTICAS:
 600V | 3A
 Package: 10 units
APPLICATION / APLICACIÓN:
 Replaces: **Delco**: 1.971.528, 1.984.459, **GM**: 52.278.221 Alternators: **Delco** 10S, 12S, 15S e 17S (42A a 65A).

DIODE TRIO GA1222


FEATURES / CARACTERÍSTICAS:
 600V | 3A
 Package: 10 units
APPLICATION / APLICACIÓN:
 Replaces: **Delco** 1876797, 10456389 For: **Delco** 30SI Series IR/EF Alternators

DIODE TRIO GA1223


FEATURES / CARACTERÍSTICAS:
 600V | 3A
 Package: 10 unit
APPLICATION / APLICACIÓN:
 Replaces: **Delco** 1977064, D3918, D3921 For: **Delco** 27SI type 100, 200 Series IR/EF

DIODE GA1224


FEATURES / CARACTERÍSTICAS:
 400V | 3A
 Package: 10 unit
APPLICATION / APLICACIÓN:
 Replaces: **Delco**: 10517358 For: Alternators **Delco** Series 21SI Alternator: **Delco**: 1117965; 19010112; 19010196; 19010105

DIODE GA1225


FEATURES / CARACTERÍSTICAS:
 1000 | 3X3A
APPLICATION / APLICACIÓN
AGRALE: Volare V8;
FOTON: Trucks with Cummins engine

DIODE



FEATURES / CARACTERÍSTICAS:

400V | 3x10A with Autostart

REPLACES / REEMPLAZA

Delco: 10517356, 10487805; Transpo: DT22

APPLICATION / APLICACIÓN

Freightliner Heavy Duty: FL 50 Caterpillar 3126, FL 50

Cummins 1998>2004; **International Medium/Heavy**

Truck: 8100-8600 Heavy

ALTERNATOR / ALTERNADOR

Delco: 19020302, 19020310

GA1226

DIODE TRIO



FEATURES / CARACTERÍSTICAS:

800V | 2A

Diods excit. compatible with GA1274

Package: 1 unit

APPLICATION / APLICACIÓN:

Replaces: Lucas 352.13.293 Alternators: Lucas

GA1293